


GLB-DLINE_ 3000K



製品図面

製品仕様

入力電圧AC-100V : (専用電源内蔵) / LED_Chip:豊田合成製5630 / 演色性:Ra84

LED品名	LED_Chip	LED個数	ランプサイズ	LED間隔(mm)	色温度(K)	全光束(lm)	全光度(cd)	消費電力(W)	入力電力(VA)	重量(g)
GLB-DLINE_2410	1 in one	240	2410	10	3000(±100)	4668	1568	44.2	48.4	959
GLB-DLINE_2260	1 in one	225	2260	10	3000(±100)	4376	1470	42.3	45.8	914
GLB-DLINE_2110	1 in one	210	2110	10	3000(±100)	4085	1373	39.5	43.9	869
GLB-DLINE_1960	1 in one	195	1960	10	3000(±100)	3793	1274	35.8	39.8	824
GLB-DLINE_1810	1 in one	180	1810	10	3000(±100)	3501	1176	32.1	35.7	779
GLB-DLINE_1660	1 in one	165	1660	10	3000(±100)	3209	1078	29.7	33	734
GLB-DLINE_1510	1 in one	150	1510	10	3000(±100)	2918	980	28.3	30	689
GLB-DLINE_1360	1 in one	135	1360	10	3000(±100)	2626	882	25.4	27.8	644
GLB-DLINE_1210	1 in one	120	1210	10	3000(±100)	2334	784	22.2	24.7	460
GLB-DLINE_1060	1 in one	105	1060	10	3000(±100)	2042	686	19.5	21.7	420
GLB-DLINE_910	1 in one	90	910	10	3000(±100)	1751	588	16.2	18	376
GLB-DLINE_760	1 in one	75	760	10	3000(±100)	1459	490	13.9	15.4	335
GLB-DLINE_610	1 in one	60	610	10	3000(±100)	1167	392	11.1	12.3	295
GLB-DLINE_460	1 in one	45	460	10	3000(±100)	875	294	8.4	9.3	250
GLB-DLINE_310	1 in one	30	310	10	3000(±100)	584	196	5.6	6.2	205

*消費電力値(W)およびその値はJIS規格の測定方法による。 *仕様は予告なく変更することがありますので予めご了承ください。 *最大連結数≒24m

OPTION品

