

棚下・間接照明用 電源内蔵LED LAMP

GLB-333									
				LED	5000K		6200K		指数
	SIZE (mm)	消費電力(W)		個数	光束(lm)	輝度(cd)	光束(lm)	輝度(cd)	
1	403 mm	3.6	W	12	216	69	217	70	0.3334
2	469 mm	4.2	W	14	252	81	253	81	0.3889
3	535 mm	4.8	W	16	288	92	289	93	0.4445
4	601 mm	5.4	W	18	324	104	325	104	0.5
5	667 mm	6	W	20	360	115	361	116	0.5556
6	733 mm	6.6	W	22	396	127	398	127	0.6112
7	799 mm	7.2	W	24	432	138	434	139	0.6667
8	865 mm	7.7	W	26	468	150	470	150	0.7223
9	931 mm	8.3	W	28	504	161	506	162	0.7778
10	997 mm	8.9	W	30	540	172	542	173	0.8334
11	1063 mm	9.5	W	32	576	184	578	185	0.8889
12	1129 mm	10.1	W	34	612	195	614	196	0.9445
13	1195 mm	10.7	W	36	648	207	650	208	1
14	1261 mm	11.3	W	38	684	218	686	219	1.0556
15	1327 mm	11.9	W	40	720	230	722	231	1.1112
16	1393 mm	12.5	W	42	756	241	759	242	1.1667
17	1459 mm	13.1	W	44	792	253	795	254	1.2223
18	1525 mm	13.7	W	46	828	264	831	265	1.2778
19	1591 mm	14.3	W	48	864	276	867	277	1.3334
20	1657 mm	14.9	W	50	900	287	903	288	1.3889
21	1723 mm	15.5	W	52	936	299	939	300	1.4445
22	1789 mm	16.1	W	54	972	310	975	311	1.5
23	1855 mm	16.7	W	56	1008	322	1011	323	1.5556
24	1921 mm	17.3	W	58	1044	333	1047	334	1.6112
25	1987 mm	17.9	W	60	1080	344	1083	346	1.6667
26	2053 mm	18.5	W	62	1116	356	1120	358	1.7223
27	2119 mm	19.1	W	64	1152	367	1156	369	1.7778
28	2185 mm	19.7	W	66	1188	379	1192	380	1.8334
29	2251 mm	20.3	W	68	1224	390	1228	392	1.8889
30	2317 mm	20.9	W	70	1260	402	1264	403	1.9445
31	2383 mm	21.5	W	72	1296	413	1300	415	2
32	2449 mm	22.1	W	74	1332	425	1336	426	2.0556
33	2515 mm	22.6	W	76	1368	436	1372	438	2.1112
34	2581 mm	23.2	W	78	1404	448	1408	449	2.1667
35	2647 mm	23.8	W	80	1440	459	1444	461	2.2223

モジュール＋7mm
66mm間隔

は予告なく変更することがありますので、予告了承くだ