



## 製品図面



## 製品仕様

入力電圧AC-100V : (専用電源内蔵) / LED\_Chip:豊田合成製5630 / 演色性:Ra84

LED品名	LED Chip	LED個数	ランプサイズ	LED間隔(mm)	色温度(K)	全光束(lm)	全光度(cd)	消費電力(W)	入力電力(VA)	重量(g)
GLB-DLINE_2410	1 in one	240	2410	10	5700(±400)	4824	1553	44.2	48.4	943
GLB-DLINE_2260	1 in one	225	2260	10	5700(±400)	4523	1456	42.3	45.8	900
GLB-DLINE_2110	1 in one	210	2110	10	5700(±400)	4221	1359	39.5	43.9	716
GLB-DLINE_1960	1 in one	195	1960	10	5700(±400)	3920	1262	35.8	39.8	674
GLB-DLINE_1810	1 in one	180	1810	10	5700(±400)	3618	1165	32.1	35.7	630
GLB-DLINE_1660	1 in one	165	1660	10	5700(±400)	3317	1068	29.7	33	590
GLB-DLINE_1510	1 in one	150	1510	10	5700(±400)	3015	971	28.3	30	547
GLB-DLINE_1360	1 in one	135	1360	10	5700(±400)	2714	874	25.4	27.8	505
GLB-DLINE_1210	1 in one	120	1210	10	5700(±400)	2411	776	22.2	24.7	460
GLB-DLINE_1060	1 in one	105	1060	10	5700(±400)	2111	680	19.5	21.7	420
GLB-DLINE_910	1 in one	90	910	10	5700(±400)	1809	582	16.2	18	376
GLB-DLINE_760	1 in one	75	760	10	5700(±400)	1508	486	13.9	15.4	335
GLB-DLINE_610	1 in one	60	610	10	5700(±400)	1206	388	11.1	12.3	295
GLB-DLINE_460	1 in one	45	460	10	5700(±400)	905	291	8.4	9.3	250
GLB-DLINE_310	1 in one	30	310	10	5700(±400)	603	194	5.6	6.2	205

\*消費電力値(W)およびその値はJIS規格の測定方法による。  
\*仕様は予告なく変更することがありますので予めご了承ください。

\*最大連結数≒24m

## OPTION品

