



製品図面

製品仕様

入力電圧AC-100V : (専用電源内蔵) / LED_Chip:豊田合成製5630 / 演色性 :Ra84

LED品名	LED_Chip	LED個数	ランプサイズ	LED間隔(mm)	色温度(K)	全光束(lm)	全光度(cd)	消費電力(W)	入力電力(VA)	重量(g)
GLB-DLINE_2410	1 in one	240	2410	10	3500(±200)	4728	1589	44.2	48.4	943
GLB-DLINE_2260	1 in one	225	2260	10	3500(±200)	4433	1489	42.3	45.8	900
GLB-DLINE_2110	1 in one	210	2110	10	3500(±200)	4137	1390	39.5	43.9	716
GLB-DLINE_1960	1 in one	195	1960	10	3500(±200)	3842	1291	35.8	39.8	674
GLB-DLINE_1810	1 in one	180	1810	10	3500(±200)	3546	1191	32.1	35.7	630
GLB-DLINE_1660	1 in one	165	1660	10	3500(±200)	3251	1092	29.7	33	590
GLB-DLINE_1510	1 in one	150	1510	10	3500(±200)	2955	993	28.3	30	547
GLB-DLINE_1360	1 in one	135	1360	10	3500(±200)	2660	894	25.4	27.8	505
GLB-DLINE_1210	1 in one	120	1210	10	3500(±200)	2360	793	22.2	24.7	460
GLB-DLINE_1060	1 in one	105	1060	10	3500(±200)	2069	695	19.5	21.7	420
GLB-DLINE_910	1 in one	90	910	10	3500(±200)	1773	596	16.2	18	376
GLB-DLINE_760	1 in one	75	760	10	3500(±200)	1478	497	13.9	15.4	335
GLB-DLINE_610	1 in one	60	610	10	3500(±200)	1182	397	11.1	12.3	295
GLB-DLINE_460	1 in one	45	460	10	3500(±200)	887	298	8.4	9.3	250
GLB-DLINE_310	1 in one	30	310	10	3500(±200)	591	199	5.6	6.2	205

*消費電力(W)およびその値はJIS規格の測定方法による。
*仕様は予告なく変更することがありますのでご了承ください。

*最大連続数≒24m

OPTION品

