



## 製品図面



## 製品仕様







入力電圧AC-100V : (専用電源内蔵) / LED\_Chip:豊田合成製5630 / 演色性 :Ra84

LED品名	LED_Chip	LED個数	ランプサイズ	LED間隔(mm)	色温度(K)	全光束(lm)	全光度(cd)	消費電力(W)	入力電力(VA)	重量(g)
GLB-DLINE_2410	1 in one	240	2410	10	4200(±200)	4800	1598	44.2	47.2	943
GLB-DLINE_2260	1 in one	225	2260	10	4200(±200)	4500	1499	42.3	45.8	900
GLB-DLINE_2110	1 in one	210	2110	10	4200(±200)	4200	1399	39.5	43.9	716
GLB-DLINE_1960	1 in one	195	1960	10	4200(±200)	3900	1299	34.5	38.3	674
GLB-DLINE_1810	1 in one	180	1810	10	4200(±200)	3600	1199	32.1	35.7	630
GLB-DLINE_1660	1 in one	165	1660	10	4200(±200)	3300	1099	29.7	33	590
GLB-DLINE_1510	1 in one	150	1510	10	4200(±200)	3000	999	28.3	30	547
GLB-DLINE_1360	1 in one	135	1360	10	4200(±200)	2700	899	25.4	27.8	505
GLB-DLINE_1210	1 in one	120	1210	10	4200(±200)	2400	799	22.2	24.7	460
GLB-DLINE_1060	1 in one	105	1060	10	4200(±200)	2100	699	19.5	21.7	420
GLB-DLINE_910	1 in one	90	910	10	4200(±200)	1800	599	16.2	18	376
GLB-DLINE_760	1 in one	75	760	10	4200(±200)	1500	500	13.9	15.4	335
GLB-DLINE_610	1 in one	60	610	10	4200(±200)	1200	400	11.1	12.3	295
GLB-DLINE_460	1 in one	45	460	10	4200(±200)	900	300	8.4	9.3	250
GLB-DLINE_310	1 in one	30	310	10	4200(±200)	600	200	5.6	6.2	205

\*消費電力値(W)およびその値はJIS規格の測定方法による。  
\*仕様は予告なく変更することがありますので予めご了承ください。

\*最大連結数≒24m

## OPTION品



2020.05.21