

※片電源	棚下・間接照明用 電源内蔵LED LAMP										
	GLB-312										
				LED	3000K		4200K		5800K		指数
	SIZE (mm)	消費電力(W)	個数	光束(lm)	輝度(cd)	光束(lm)	輝度(cd)	光束(lm)	輝度(cd)		
1	285	mm	4.7 W	22	286	92	352	113	396	127	0.2292
2	310	mm	5.1 W	24	312	100	384	123	432	138	0.25
3	335	mm	5.6 W	26	338	108	416	133	468	150	0.2709
4	360	mm	6 W	28	364	116	448	143	504	161	0.2917
5	385	mm	6.4 W	30	390	125	480	153	540	172	0.3125
6	410	mm	6.8 W	32	416	133	512	164	576	184	0.3334
7	435	mm	7.2 W	34	442	141	544	174	612	195	0.3542
8	460	mm	7.7 W	36	468	150	576	184	648	207	0.375
9	485	mm	8.1 W	38	494	158	608	194	684	218	0.3959
10	510	mm	8.5 W	40	520	166	640	204	720	230	0.4167
11	535	mm	8.9 W	42	546	174	672	215	756	241	0.4375
12	560	mm	9.3 W	44	572	183	704	225	792	253	0.4584
13	585	mm	9.8 W	46	598	191	736	235	828	264	0.4792
14	610	mm	10.2 W	48	624	199	768	245	864	276	0.5
15	635	mm	10.6 W	50	650	208	800	255	900	287	0.5209
16	660	mm	11 W	52	676	216	832	265	936	299	0.5417
17	685	mm	11.4 W	54	702	224	864	276	972	310	0.5625
18	710	mm	11.9 W	56	728	232	896	286	1008	322	0.5834
19	735	mm	12.3 W	58	754	241	928	296	1044	333	0.6042
20	760	mm	12.7 W	60	780	249	960	306	1080	344	0.625
21	785	mm	13.1 W	62	806	257	992	316	1116	356	0.6459
22	810	mm	13.5 W	64	832	265	1024	327	1152	367	0.6667
23	835	mm	14 W	66	858	274	1056	337	1188	379	0.6875
24	860	mm	14.4 W	68	884	282	1088	347	1224	390	0.7084
25	885	mm	14.8 W	70	910	290	1120	357	1260	402	0.7292
26	910	mm	15.2 W	72	936	299	1152	367	1296	413	0.75
27	935	mm	15.6 W	74	962	307	1184	378	1332	425	0.7709
28	960	mm	16.1 W	76	988	315	1216	388	1368	436	0.7917
29	985	mm	16.5 W	78	1014	323	1248	398	1404	448	0.8125
30	1010	mm	16.9 W	80	1040	332	1280	408	1440	459	0.8334
31	1035	mm	17.3 W	82	1066	340	1312	418	1476	471	0.8542
32	1060	mm	17.7 W	84	1092	348	1344	429	1512	482	0.875
33	1085	mm	18.2 W	86	1118	357	1376	439	1548	493	0.8959
34	1110	mm	18.6 W	88	1144	365	1408	449	1584	505	0.9167
35	1135	mm	19 W	90	1170	373	1440	459	1620	516	0.9375
36	1160	mm	19.4 W	92	1196	381	1472	469	1656	528	0.9584
37	1185	mm	19.9 W	94	1222	390	1504	479	1692	539	0.9792
38	1210	mm	20.3 W	96	1248	398	1536	490	1728	551	1
39	1235	mm	20.7 W	98	1274	406	1568	500	1764	562	1.0209
40	1260	mm	21.1 W	100	1300	415	1600	510	1800	574	1.0417
41	1285	mm	21.5 W	102	1326	423	1632	520	1836	585	1.0625
42	1310	mm	22 W	104	1352	431	1664	530	1872	597	1.0834
43	1335	mm	22.4 W	106	1378	439	1696	541	1908	608	1.1042
44	1360	mm	22.8 W	108	1404	448	1728	551	1944	620	1.125
45	1385	mm	23.2 W	110	1430	456	1760	561	1980	631	1.1459
46	1410	mm	23.6 W	112	1456	464	1792	571	2016	643	1.1667
47	1435	mm	24.1 W	114	1482	472	1824	581	2052	654	1.1875
48	1460	mm	24.5 W	116	1508	481	1856	592	2088	665	1.2084
49	1485	mm	24.9 W	118	1534	489	1888	602	2124	677	1.2292
50	1510	mm	25.3 W	120	1560	497	1920	612	2160	688	1.25
51	1535	mm	25.7 W	122	1586	506	1952	622	2196	700	1.2709
52	1560	mm	26.2 W	124	1612	514	1984	632	2232	711	1.2917
53	1585	mm	26.6 W	126	1638	522	2016	643	2268	723	1.3125
54	1610	mm	27 W	128	1664	530	2048	653	2304	734	1.3334
55	1635	mm	27.4 W	130	1690	539	2080	663	2340	746	1.3542
56	1660	mm	27.8 W	132	1716	547	2112	673	2376	757	1.375
57	1685	mm	28.3 W	134	1742	555	2144	683	2412	769	1.3959
58	1710	mm	28.7 W	136	1768	564	2176	693	2448	780	1.4167
59	1735	mm	29.1 W	138	1794	572	2208	704	2484	792	1.4375
60	1760	mm	29.5 W	140	1820	580	2240	714	2520	803	1.4584
61	1785	mm	29.9 W	142	1846	588	2272	724	2556	815	1.4792
62	1810	mm	30.4 W	144	1872	597	2304	734	2592	826	1.5
63	1835	mm	30.8 W	146	1898	605	2336	744	2628	837	1.5209
64	1860	mm	31.2 W	148	1924	613	2368	755	2664	849	1.5417
65	1885	mm	31.6 W	150	1950	622	2400	765	2700	860	1.5625
66	1910	mm	32 W	152	1976	630	2432	775	2736	872	1.5834
67	1935	mm	32.5 W	154	2002	638	2464	785	2772	883	1.6042
68	1960	mm	32.9 W	156	2028	646	2496	795	2808	895	1.625
69	1985	mm	33.3 W	158	2054	655	2528	806	2844	906	1.6459
70	2010	mm	33.7 W	160	2080	663	2560	816	2880	918	1.6667
71	2035	mm	34.2 W	162	2106	671	2592	826	2916	929	1.6875
72	2060	mm	34.6 W	164	2132	679	2624	836	2952	941	1.7084
73	2085	mm	35 W	166	2158	688	2656	846	2988	952	1.7292
74	2110	mm	35.4 W	168	2184	696	2688	857	3024	964	1.75
75	2135	mm	35.8 W	170	2210	704	2720	867	3060	975	1.7709
76	2160	mm	36.3 W	172	2236	713	2752	877	3096	986	1.7917
77	2185	mm	36.7 W	174	2262	721	2784	887	3132	998	1.8125
78	2210	mm	37.1 W	176	2288	729	2816	897	3168	1009	1.8334
79	2235	mm	37.5 W	178	2314	737	2848	908	3204	1021	1.8542
80	2260	mm	37.9 W	180	2340	746	2880	918	3240	1032	1.875
81	2285	mm	38.4 W	182	2366	754	2912	928	3276	1044	1.8959
82	2310	mm	38.8 W	184	2392	762	2944	938	3312	1055	1.9167
83	2335	mm	39.2 W	186	2418	771	2976	948	3348	1067	1.9375
84	2360	mm	39.6 W	188	2444	779	3008	958	3384	1078	1.9584
85	2385	mm	40 W	190	2470	787	3040	969	3420	1090	1.9792
86	2410	mm	40.5 W	192	2496	795	3072	979	3456	1101	2
モジュール+10mm 25mm間隔											
仕様は予告なく変更することがありますので、ご了承ください。				2020.05.11							

※片側電源のみ